

1770 RPM

ENCLOSED TYPE IMPELLER

21XKL

NUMBER  
OF STAGESEFFICIENCY CHANGE  
(NO. OF POINTS)1  
2  
3HORSEPOWER WILL BE AFFECTED  
BY CHANGE IN EFFICIENCY

## PUMP DATA

Shaft Dia.(IN)  
 Maximum Sphere (IN)  
 Maximum Head (FT)\*  
 Min. Submergence (IN)\*\*  
 Impeller Weight (LBS)  
 Thrust Constant (K)  
 Thrust Bal Const. (K)  
 Bowl O.D.(IN.)  
 Bowl Height (IN.)  
 Bell DIA. (T) (IN.)  
 Strainer height (IN.)  
 Impeller C-line(X)(IN.)  
 Eye Area (IN<sup>2</sup>)

## NOTES

Performance indicated based on cold water with specific gravity of 1.0.

\* Standard Construction.

\*\* Minimum submergence over lip of bell to prevent vortexing.

Efficiency improvements are available in certain instances. Please contact the factory.

PERFORMANCE FOR:

FOR PERFORMANCE  
CONTACT FACTORY

BOWL HEAD (FT)

NPSH REQ'D (FT)

BOWL HP.

CAPACITY (USGPM)