





Column	Nom. Size	Max. GPM	*A* Flanged	*B* Threaded
Optional	8"	1500	11.50"	11.50"
Standard	10"	3000	15.00"	11.62"
Optional	12"	5000	16.00"	13.75"

RATINGS	
Max. Pressure = 392 psi based on Class 30 Iron bowls	
Impeller and Shaft Weight = 37.0 pounds per stage	
Pump Shaft Diameter = 2.19 inches	
Max. HP. = 383 with 416 SS Pump Shaft	
Line Shaft Size	1.50 1.69 1.94 2.19
Line Shaft H.P.	133 192 293 383

Additional Data	
Max. Operating Speed.	2100
Max. No. of Stages	10
Max. Sphere Size	.50
End Play	.75
WR 2 Per Stage	2.61
Bowl Ring Clearance	.004 - .006
Impeller Running Clearance (3)	.250



(1) Minimum submergence required to prevent vortex formation. The submergence needed to provide adequate NPSH to the first stage. Impeller may be greater or less than shown. The larger of the two values must be used to determine actual minimum allowable submergence.

- (2) Location of eye of first stage impeller. Used to calculate NPSH. This is also the minimum priming submergence. (See note 1).
- (3) Vertical Impeller to Bowl running clearance after shaft stretch.
- (4) For Suction Case dimensions see sheets 20.26 and 20.29.