





Column	Nom. Size	Max. GPM	"A" Flanged	"B" Threaded
Optional	12"	5000	16.50"	13.62"
Standard	14"	7000	19.00"	15.00"
Optional	16"	9000	21.50"	16.38"

RATINGS				
Max. Pressure = 375 psi based on Class 30 Iron bowls				
Impeller and Shaft Weight = 45.0 pounds per stage				
Pump Shaft	Diameter = 2.19 inches			
	Max. HP. = 383 with 416 SS Pump Shaft			
Line Shaft Size	1.50	1.69	1.94	2.19
Line Shaft H.P.	133	192	293	383

Additional Data	
Max. Operating Speed	1800
Max. No. of Stages	9
Max. Sphere Size	.63
End Play	.81
WR 2 Per Stage	2.91
Bowl Ring Clearance	.003 - .005
Impeller Running Clearance (3)	.250



- (1) Minimum submergence required to prevent vortex formation. The submergence needed to provide adequate NPSH to the first stage. Impeller may be greater or less than shown. The larger of the two values must be used to determine actual minimum allowable submergence.

- (2) Location of eye of first stage impeller. Used to calculate NPSH. This is also the minimum priming submergence. (See note 1).
- (3) Vertical Impeller to Bowl running clearance after shaft stretch.