





Column	Nom. Size	Max. GPM	"A" Flanged	"B" Threaded
Optional	8"	1500	11.38"	11.38"
Standard	10"	3000	13.50"	11.75"

RATINGS	
Max. Pressure = 300 psi based on Class 30 Iron bowls	
Impeller and Shaft Weight = 16.0 pounds per stage	
Pump Shaft	Diameter = 1.50 inches
	Max. HP. = 200 with 416 SS Pump Shaft
Line Shaft Size	1.00 1.25 1.50
Line Shaft H.P.	57 115 200

Additional Data	
Max. Operating Speed	2100
Max. No. of Stages	18
Max. Sphere Size	1.05
End Play	.56
WR 2 Per Stage	CF
Bowl Ring Clearance	N/A
Impeller Running Clearance (3)	.010 - .015

- (1) Minimum submergence required to prevent vortex formation. The submergence needed to provide adequate NPSH to the first stage. Impeller may be greater or less than shown. The larger of the two values must be used to determine actual minimum allowable submergence.

CF-Contact Factory
N/A-Not Available



- (2) Location of eye of first stage impeller. Used to calculate NPSH. This is also the minimum priming submergence. (See note 1).
- (3) Vertical impeller to Bowl running clearance after shaft stretch.