





Column	Nom. Size	Max. GPM	"A" Flanged	"B" Threaded
Optional	12"	5000	16.00"	16.00"
Standard	14"	7000	17.25"	17.25"
Optional	16"	9000	19.50"	-

RATINGS				
Max. Pressure = 490 psi based on Class 30 Iron bowls				
Impeller and Shaft Weight = 130.0 pounds per stage				
Pump Shaft Diameter = 2.44 inches				
Max. HP. = 805 with 416 SS Pump Shaft				
Line Shaft Size	1.69	1.94	2.19	2.44
Line Shaft H.P.	288	440	575	805

Additional Data	
Max. Operating Speed	2100
Max. No. of Stages	10
Max. Sphere Size	1.57
End Play	1.53
WR 2 Per Stage	16.90
Bowl Ring Clearance	.006 - .008
Impeller Running Clearance (3)	.250



- (1) Minimum submergence required to prevent vortex formation. The submergence needed to provide adequate NPSH to the first stage. Impeller may be greater or less than shown. The larger of the two values must be used to determine actual minimum allowable submergence.

- (2) Location of eye of first stage impeller. Used to calculate NPSH. This is also the minimum priming submergence. (See note 1).
- (3) Vertical impeller to Bowl running clearance after shaft stretch.