



Company: Bonneville Power Administration

Name:

Date: 2/8/2007

Selection: FPI

Pump:

Size: AF48-42-392

Type: AXIAL FLOW
Synch speed: 400 rpm

Curve:

Specific Speeds:

Dimensions:

Speed: 392 rpm
Line: A (48)

Impeller:

Ns: ---
Nss: ---

Suction: --- in
Discharge: --- in

Search Criteria:

Flow: --- US gpm

Head: --- ft

Fluid:

Water
Density: 62.25 lb/ft³
Viscosity: 1.105 cP
NPSHa: --- ft

Temperature: 60 °F
Vapor pressure: 0.2563 psi a
Atm pressure: 14.7 psi a

Motor:

Standard: NEMA
Enclosure: TEFC

--- hp
Speed: ---
Frame: ---


Sizing criteria: Max Power on Design Curve

Pump Limits:

Temperature: --- °F
Pressure: --- psi g
Sphere size: --- in

Power: --- hp
Eye area: --- in²

---- Data Point ----	
Flow:	57909 US gpm
Head:	16.7 ft
Eff:	84.5%
Power:	290 hp
NPSHr:	21.2 ft
---- Design Curve ----	
Shutoff head:	20.8 ft
Shutoff dP:	8.99 psi
Min flow:	--- US gpm
BEP:	84.5% @ 57909 US gpm
NOL power:	335 hp @ 44097 US gpm
-- Max Curve --	
Max power:	335 hp @ 44097 US gpm



The performance is guaranteed for the design point only when pumping clean water at 85 degrees F. Consult factory for certified performance curve.

Performance Evaluation:

Flow US gpm	Speed rpm	Head ft	Efficiency %	Power hp	NPSHr ft
68080	392	10.2	78.3	224	30.5
56733	392	17.3	84.2	295	20.6
45386	392	21.4	73.5	333	19.2
34040	392	---	---	---	---
22693	392	---	---	---	---