




No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-4	IMP. - C.I.	-2
2	-2	IMP. - NI-RI	-1
3	0	BOWL - BRZ.	-1
4		BOWL - NI-R.	-1


12RKBH**1170** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE STAGE | 1 STAGES

PUMP PERFORMANCE

EYE AREA - SQ. IN.	= 16.4	IMPELLER WT. - LBS.	= 15.3
WR. PER IMPELLER LB.-FT. ²	= 1.00	ONE STAGE WT. - LBS.	= 278
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 105
MAX. NO. STD. STAGES	= 22	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 500	DISCH. - IN.	= 8, 10
STD. LATERAL - IN.	= 0.70	SUCTION - IN.	= 8
STD. SHAFT DIA. - IN.	= 1.687	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= 18	ADD 9.38" PER ADDITIONAL STAGE	



LB1170-2RKBH-211C