





No. Stages	Eff. Change	MATERIAL	Eff. Change
1		IMP. - C.I.	-2
2		IMP. - NI-RI	-1
3		BOWL - BRZ.	-1
4		BOWL - NI-R.	-1

11DWH**1770** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 5 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 5 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

 ONE ()
 STAGE STAGES
PUMP PERFORMANCE

EYE AREA - SQ. IN.	= 14.71	IMPELLER WT. - LBS.	= 13.7
WR* PER IMPELLER LB.-FT. ²	= 0.75	ONE STAGE WT. - LBS.	= 232
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 110
MAX. NO. STD. STAGES	= 20	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 600	DISCH. - IN.	= 8.10
STD. LATERAL - IN.	= 1.50	SUCTION - IN.	= 8
STD. SHAFT DIA. - IN.	= 1.687	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. IN.	= -----	BOWL CONN. FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= -----	ADD - - - " PER ADDITIONAL STAGE	



LB17701C/W2110