




No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-2
2	-1	IMP. - NI-RI	-1
3	0	BOWL - BRZ.	-1
4		BOWL - NI-R.	-1


13DWEH**1770**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE[]
STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 17	IMPELLER WT. - LBS.	= 25
WR² PER IMPELLER LB.-FT.²	= 1.37	ONE STAGE WT. - LBS.	= 410
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 190
MAX. NO. STD. STAGES	= 24	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 880	DISCH. - IN.	= 8, 10
STD. LATERAL - IN.	= 1.68	SUCTION - IN.	= 8
STD. SHAFT DIA. - IN.	= 1.937	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. - FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= -----	ADD - - - -" PER ADDITIONAL STAGE.	



LB177013DWEH2110