

CURVE data




No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-1.0	IMP. - C.I.	-1.0
2	NO CHG.		
3	NO CHG.		
4	NO CHG.		


32BRHC

580 R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.



EYE AREA - SQ. IN.	= 166.8	IMPELLER WT. - LBS.	= 292
WR ² PER IMPELLER LB.-FT. ²	= 149.80	ONE STAGE WT. - LBS.	= 3300
MAX. SPHERE SIZE	= 1.88	ADD'L STAGE WT. - LBS.	= 1650
MAX. NO. STD. STAGES	= 7	IMPELLER NUMBER	= YT5PA99
MAX. OPERATING - P.S.I.	= - - - -	DISCH. - IN.	= 24
STD. LATERAL - IN.	= 1.06	SUCTION - IN.	= - - - -
STD. SHAFT DIA. - IN.	= 5	MAX. LATERAL - IN.	= - - - -
MAX. SHAFT DIA. - IN.	= - - - -	BOWL / IMP. CONN.	= - - - -
MIN. SUBMERGENCE - IN.	= 50	ADD 24-1/4" PER ADDITIONAL STAGE.	



Curves reflect typical performance, refer to factory for certification.