




No. Stages	Eff. Change	MATERIAL	Eff. Change
1	NO CHG.	IMP. - C.I.	-1.0
2	NO CHG.		
3	NO CHG.		
4	NO CHG.		


27BRM**705**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE()
STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 139.36	IMPELLER WT. - LBS.	= 225
WR* PER IMPELLER LB.-FT. ²	= 80.0	ONE STAGE WT. - LBS.	= 1388
MAX. SPHERE SIZE	= 2.75	ADD'L STAGE WT. - LBS.	= 940
MAX. NO. STD. STAGES	= 7	IMPELLER NUMBER	= T7MK892A
MAX. OPERATING - P.S.I.	= -----	DISCH. - IN.	= 20
STD. LATERAL - IN.	= 1.25	SUCTION - IN.	= -----
STD. SHAFT DIA. - IN.	= 3.16	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL / IM. CONN. -	= -----
MIN. SUBMERGENCE - IN.	= 42	ADD 21-1/2" PER ADDITIONAL STAGE.	



Curves reflect typical performance; refer to factory for certification