


CHANGE EFFICIENCY AS FOLLOWS	NUMBER OF POINTS	FOR NUMBER OF STAGES
Lower	1	5
"	2	2
"	4	1
NOTE: ANY CHANGE IN EFFICIENCY AFFECTS EITHER THE HEAD OR HORSE POWER CORRESPONDINGLY		

BOWL T8L265E



HYDRAULIC PERFORMANCE GUARANTEED AT THE DESIGNATED POINT ONLY.	CURVE NO.	IMPELLER NO.	IMPELLER DIA.	TAKEN FROM
Efficiency must be reduced for bronze & special material bowls - See Appli- cation Section		V1440B	4-1/4	27695

PEERLESS PUMP DIVISION

FOOD MACHINERY AND CHEMICAL
CORPORATION
LOS ANGELES 31, CALIFORNIA



PERFORMANCE PER STAGE

6 LA

1760


R. P. M.

SHEET NO. 2812041

CHANGE EFFICIENCY AS FOLLOWS	NUMBER OF POINTS	FOR NUMBER OF STAGES
LOWER	1	5
"	2	2
"	4	1

NOTE: ANY CHANGE IN EFFICIENCY
AFFECTS EITHER THE HEAD OR
HORSE POWER CORRESPONDINGLY

BOWL 784265



HYDRAULIC PERFORMANCE GUARANTEED AT THE DESIGNATED POINT ONLY AND IS CONTINGENT ON WELL PROPERLY FURNISHING PUMP WITH NON-AERATED OR NON- GASEOUS WATER FREE FROM AB- RASIVES. PUMP BOWLS MUST BE PROPERLY ADJUSTED FOR THE HEAD AT WHICH THEY OPERATE AND MUST BE SUBMERGED.	CURVE NO.	IMPELLER NO.	IMPELLER DIA.	TAKEN FROM	PEERLESS PUMP DIVISION FOOD MACHINERY CORPORATION LOS ANGELES 31, CALIF. 	PERFORMANCE PER STAGE	
	1	V1440B	4 1/4"	20378		6 LA	DEEP WELL
	2					1760	TURBINE PUMP
	3						R. P. M.
						SHEET NO.	R-1275