


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE

 Fairbanks Morse Pump	No. Stages	Eff. Change	MATERIAL	Eff. Change	12D	1170	R.P.M.
	1	-4	IMP. - C.I.	-2	SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.		
	2	-2	IMP. - NI-R	-1			
	3	0	BOWL - BRZ	-1			
	4		BOWL - NI-R	-1			



EYE AREA - SQ. IN.	= 16.4	IMPELLER WT. - LBS.	= 15.3
WHP PER IMPELLER LB.-FT. ³	= 1.00	ONE STAGE WT. - LBS.	= 278
MAX. SPHERE SIZE	= ----	ADD'L STAGE WT. - LBS.	= 105
MAX. NO. STD. STAGES	= 22	IMPELLER NUMBER	= ----
MAX. OPERATING - P.S.I.	= 580	DISCH. - IN.	= 8, 10
STD. LATERAL - IN.	= 0.70	SUCTION - IN.	= 8
STD. SHAFT DIA. - IN.	= 1.687	MAX. LATERAL - IN.	= ----
MAX. SHAFT DIA. - IN.	= ----	BOWL CONN. FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= 18	ADD 9.38" PER ADDITIONAL STAGE.	

