


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE

12MC
7000

1170
RPM

IMPELLER
T5EB92




EFFICIENCY CORRECTIONS (1)

NUMBER OF STAGES	EFFICIENCY CHANGE
1	- 3.0 POINTS
2	- 2.0 POINTS
3	- 1.0 POINTS
4	- 0.5 POINTS
5	NO CHANGE
6 OR MORE	NO CHANGE

BOWL MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 2.0 POINTS
ENAMELED C.I.	NO CHANGE

IMPELLER MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 2.0 POINTS
BRONZE	NO CHANGE
ENAMELED C.I.	NO CHANGE

DIMENSIONS (Inches)



TECHNICAL DATA

DATA	VALUE
MAXIMUM OPERATING SPEED	2250 RPM
MAXIMUM NUMBER OF STAGES	23**
PUMP SHAFT DIAMETER	1 1/8 IN.
IMPELLER EYE AREA	20.42 SQ. IN.
MAXIMUM SPHERE SIZE	.56 IN.
K ₁ (THRUST FACTOR)	8 LBS./FT.
K ₂ (ROTOR WT. PER STAGE)	12.60 LBS.
BOWL WT. (FIRST STAGE)	280 LBS.
BOWL WT. (EACH ADD'L. STAGE)	100 LBS.
ALLOWABLE SHAFT STRETCH	.88 IN. **
WK ² (FIRST STAGE)	1.46 LBS.-FT. 2
WK ² (EACH ADD'L. STAGE)	1.42 LBS.-FT. 2
BOWL RING CLEARANCE	.010/.015 IN.

**These are nominal values. Refer to "Application and Reference Data" for information further limiting or extending these values.

(1) Refer to "Application and Reference Data" for head correction.

*Add 9.12 for each additional stage.