


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE



**28XH
6920
1170
RPM**

IMPELLER
T5NA268


EFFICIENCY CORRECTIONS (1)

NUMBER OF STAGES	EFFICIENCY CHANGE
1	- 1.0 POINTS
2	NO CHANGE
3	NO CHANGE
4	NO CHANGE
5	NO CHANGE
6 OR MORE	NO CHANGE

BOWL MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 1.0 POINTS
EPOXIED C. I.	NO CHANGE

IMPELLER MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 1.0 POINTS
BRONZE	NO CHANGE
EPOXIED C. I.	NO CHANGE

DIMENSIONS (Inches)



TECHNICAL DATA

DATA	VALUE
MAXIMUM OPERATING SPEED	1200 RPM
MAXIMUM NUMBER OF STAGES	7**
PUMP SHAFT DIAMETER	4 IN.
IMPELLER EYE AREA	197.2 SQ. IN.
MAXIMUM SPHERE SIZE	1.91 IN.
K _t (THRUST FACTOR)	76 LBS./FT.
K _a (ROTOR WT. PER STAGE)	190 LBS.
BOWL WT. (FIRST STAGE)	2420 LBS.
BOWL WT. (EACH ADD'L. STAGE)	1210 LBS.
ALLOWABLE SHAFT STRETCH	1.06 IN.**
WK ² (FIRST STAGE)	107.31 LBS.-FT. ²
WK ² (EACH ADD'L. STAGE)	104.88 LBS.-FT. ²
BOWL RING CLEARANCE	.018/.022 IN.

**These are nominal values. Refer to "Application and Reference Data" for information further limiting or extending these values.

(1) Refer to "Application and Reference Data" for head correction.

*Add 24.50 for each additional stage.

FAIRBANKS MORSE PUMPS