


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE



**12XH
7000
1770
RPM**

IMPELLER
T5EA268

EFFICIENCY CORRECTIONS (1)


NUMBER OF STAGES	EFFICIENCY CHANGE
1	- 3.0 POINTS
2	- 2.0 POINTS
3	- 1.0 POINTS
4	NO CHANGE
5	NO CHANGE
6	NO CHANGE

BOWL MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 2.0 POINTS
ENAMELED C.I.	NO CHANGE

IMPELLER MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 2.0 POINTS
BRONZE	NO CHANGE
ENAMELED C.I.	NO CHANGE

(1) Refer to "Application and Reference Data" for head correction.

DIMENSIONS (Inches)



*Add 11.88 for each additional stage.

TECHNICAL DATA

DATA	VALUE
MAXIMUM OPERATING SPEED	2300 RPM
MAXIMUM NUMBER OF STAGES	15 **
IMPELLER SHAFT DIAMETER	1 15/16 IN.
IMPELLER EYE AREA	33.38 SQ. IN.
MAXIMUM SPHERE SIZE	.81 IN.
K _t (THRUST FACTOR)	12.00 LBS./FT.
K _a (ROTOR WT. PER STAGE)	19.00 LBS./FT.
BOWL WT. (FIRST STAGE)	340 LBS.
BOWL WT. (EACH ADD'L. STAGE)	130 LBS.
ALLOWABLE SHAFT STRETCH	.88 IN.**
WK ² (FIRST STAGE)	2.67 LBS.-FT. ²
WK ² (EACH ADD'L. STAGE)	2.60 LBS.-FT. ²
BOWL RING CLEARANCE	.011/.016 IN.

**These are nominal values. Refer to "Application and Reference Data" for information further limiting or extending these values.