


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE



**8M
7000
1770
RPM**

ENCLOSED
IMPELLER
T7CA92

EFFICIENCY CORRECTIONS⁽¹⁾


NUMBER OF STAGES	EFFICIENCY CHANGE
1	-7.0 POINTS
2	-3.0 POINTS
3	-1.0 POINTS
4	NO CHANGE
5	NO CHANGE
6 OR MORE	NO CHANGE

BOWL MATERIAL	EFFICIENCY CHANGE
CAST IRON	-2.0 POINTS
ENAMELED C.I.	NO CHANGE

IMPELLER MATERIAL	EFFICIENCY CHANGE
CAST IRON	-1.0 POINTS
BRONZE	NO CHANGE
ENAMELED C.I.	NO CHANGE

(1) Refer to "Application and Reference Data" for head correction.

DIMENSIONS (Inches)



*Add 6.68 for each additional stage.

TECHNICAL DATA

DATA	VALUE
MAXIMUM OPERATING SPEED	3600 RPM
MAXIMUM NUMBER OF STAGES	32**
PUMP SHAFT DIAMETER	1 1/8 IN.
IMPELLER EYE AREA	6.93 SQ. IN.
MAXIMUM SPHERE SIZE	.56 IN.
K _t (THRUST FACTOR)	2.32 LBS./FT.
K _r (ROTOR WT. PER STAGE)	5.25 LBS.
BOWL WT. (FIRST STAGE)	82 LBS.
BOWL WT. (EACH ADD'L. STAGE)	31 LBS.
ALLOWABLE SHAFT STRETCH	.37 IN.**
WK ¹ (FIRST STAGE)	.17 LBS.-FT. ²
WK ² (EACH ADD'L. STAGE)	.16 LBS.-FT. ²
BOWL RING CLEARANCE	.014/.018 IN.

** These are nominal values. Refer to "Application and Reference Data" for information further limiting or extending these values.

*** This value is the minimum submergence required to prevent vortexing only. This value may need to be increased to provide adequate NPSHA.

FAIRBANKS MORSE PUMPS