


VERTICAL TURBINE PUMPS SINGLE STAGE PERFORMANCE

**24XH
6920**

**880
RPM**

IMPELLER
T5MB268




EFFICIENCY CORRECTIONS (1)

NUMBER OF STAGES	EFFICIENCY CHANGE
1	- 2.0 POINTS
2	- 1.0 POINTS
3	NO CHANGE
4	NO CHANGE
5	NO CHANGE
6 OR MORE	NO CHANGE

BOWL MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 1.0 POINTS
EPOXIED C.I.	NO CHANGE

IMPELLER MATERIAL	EFFICIENCY CHANGE
CAST IRON	- 1.0 POINTS
BRONZE	NO CHANGE
EPOXIED C.I.	NO CHANGE

DIMENSIONS (Inches)



TECHNICAL DATA

DATA	VALUE
MAXIMUM OPERATING SPEED	1300 RPM
MAXIMUM NUMBER OF STAGES	9**
PUMP SHAFT DIAMETER	3 7/8 IN.
IMPELLER EYE AREA	153.7 SQ. IN.
MAXIMUM SPHERE SIZE	1.88 IN.
K ₁ (THRUST FACTOR)	59 LBS./FT
K ₂ (ROTOR WT. PER STAGE)	140 LBS
BOWL WT. (FIRST STAGE)	1760 LBS
BOWL WT. (EACH ADD'L STAGE)	880 LBS
ALLOWABLE SHAFT STRETCH	1.06 IN. **
WK ₂ (FIRST STAGE)	51.08 LBS.-FT. ²
WK ₂ (EACH ADD'L STAGE)	49.83 LBS.-FT. ²
BOWL RING CLEARANCE	.015/.021 IN.

**These are nominal values. Refer to "Application and Reference Data" for information further limiting or extending these values.

(1) Refer to "Application and Reference Data" for head correction.

*Add 21.88 for each additional stage.