

**SST — Submersible Turbine
NOMINAL MULTI-STAGE PER STAGE DATA**


MODEL 6B 240 (R)

3500 RPM

60 HZ

Minimum Well Size (inches) 6


TOTAL DYNAMIC HEAD — FEET



No. Of Stages	Change Eff. %
1	(a)
2	-7
4	-5
6	-3
8	-1
10	0

(a) Consult Factory for Single Stage Data

Trim	Min. Req'd. H.P.
A	4.3
B	4.0
C	3.6



Note: Efficiencies Reflect Cast Iron Bowls
Bowl Type: Threaded
Impeller Type: Enclosed
K Factor = 2.8

	4" Motor Mount	6" Motor Mount
A — One Stage Pump Length (in.)	18-13/16	17-9/16
B — Additional Stage Length (in.)	4-1/4	4-1/4
C — Max. Bowl Diameter (in.)	5-1/2	5-1/2
D — Max. Pump Diameter (in.)	6	6
E — Min. Submergence (in.)	18	18
F — Discharge Tap (in.) NPT	4	4
Shipping Weight (lbs.) Single Stage	55	50
Additional Weight Per Stage	15-1/2	15-1/2



**RED JACKET®
PUMPS**

A Marley Pump Company

P.O. Box 3888 Davenport Iowa 52808