


TOTAL HEAD FEET



CAPACITY U.S. G.P.M.

DEEP WELL SUBMERSIBLE TURBINE

CURVE No. ST1128

IMPELLER DATA


IMPELLER No. P5-43DC
 TYPE Enclosed - Brass
 DIAMETER 5.420 x 26°
 EFFECTIVE EYE AREA 14.28 Sq. Inches
 NUMBER OF VANES 7
 THRUST CONSTANT K 6.63 Lbs./Ft. of Head
 WR^2 Lbs. Ft.²
 WEIGHT 10 Lbs.
 EYE FLUID VELOCITY .023 Ft./Sec./G.P.M.
 PERIPHERAL VELOCITY 15.05 Ft./Sec./Inch of Impeller Dia.

BOWL ASSEMBLY DATA

BOWL No. P101-65E (C.I. Enameled)
 CONNECTION TYPE Bolted
 DISCHARGE TAPPING 8"
 PUMP SHAFT DIA. 1½"
 NUMBER OF STAGES 1

PERFORMANCE DATA

PERFORMANCE CURVE BASED ON 6" MOTOR
 WITH SPEED OF 3435 RPM AT BEP. USE OF
 DIFFERENT SIZE MOTOR, OR DIFFERENT SPEED
 CHARACTERISTIC WILL CHANGE PERFORMANCE.



DIMENSIONS

A-OVERALL LIQUID END LENGTH
 B-SUCTION CONNECTION LENGTH
 C-STAGE LENGTH
 D-DISCHARGE CONNECTION LENGTH
 E-BOWL DIAMETER
 F-DIAMETER ACROSS LEAD GUARD
 G-MOTOR DIAMETER
 H-MOTOR LENGTH
 J-OVERALL PUMP LENGTH-INCLUDING MOTOR

DIMENSION	A	B	C	D	E	F	G	H	J
INCHES	33-1/8	15-7/8	8-5/8	8-19/32	9-5/8	10-3/16	5-1/2	40-9/16	73-11/16

UNIT WEIGHTS - POUNDS

MOTOR SIZE	6"	
PUMP INCLUDING MOTOR	480	
LIQUID END ONLY	180	