




**1770 RPM
SINGLE STAGE PERFORMANCE**

**MODEL 10ECM
ENCLOSED IMPELLER
STANDARD CONSTRUCTION**

☐ STAGES REQUIRED



PUMP HYDRAULIC PERFORMANCE IS BASED ON STANDARD MATERIALS OF CONSTRUCTION HANDLING COLD, CLEAR, FRESH, NONAERATED WATER, FREE OF FOREIGN MATERIALS. LOSSES ARE NOT INCLUDED.



STANDARD DIMENSIONS

	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	T	W	X	Y
IN.	23 3/4	21 1/4	8 1/2	9 3/4	4 1/2	4 3/4	4 1/2	6 3/4	9	9 3/4	16 1/4	6	1 1/2	14 1/2	16 3/4	4	10 3/4	10	6
MM.	603.3	549.3	215.9	244.5	114.3	117.5	114.3	171.5	228.6	244.5	412.8	152.4	38.1	368.3	422.3	101.6	257.2	254	152.4

STANDARD DATA

IMPELLER NO.	SPECIFIC SPEED	THRUST FACTOR K	SHAFT DIAMETER	STANDARD AXIAL CLEARANCE	MAX. STAGES	MAX. PRESSURE	DISCHARGE SIZE	SUCTION SIZE	SINGLE STAGE WEIGHTS		WEIGHT EACH ADDITIONAL STAGE
									THREADED SUCTION	BELL SUCTION	
310821	2736	8.3 lb/ft	1.500 in	0.6875 in	25	458 psi	5, 6, 8 in	6, 8 in	264 lb	247 lb	75 lb
		121.2 N/m	38.1 mm	17.5 mm		3158 kPa	127, 152, 203 mm	152, 203 mm	119.7 Kg	112 Kg	34 Kg

Refer to Section C and I for K-Factor, optional materials, construction and engineering data.