


CURVE data

Veri-Line®


No Stages	Eff Change	MATERIAL	Eff Change
1	-4	IMP. - C.I.	-1
2	-2	IMP. - NI-RI	-1
3	-1	BOWL - BRZ.	-2
4	0	BOWL - NI-R.	-2

12FHH**1170** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 4 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 4 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.



EYE AREA - SQ. IN.	= 37.4	IMPELLER WT. - LBS.	= 16
WRP PER IMPELLER LB.-FT. ³	= 1.68	ONE STAGE WT. - LBS.	= 240
MAX. NO. STD. STAGES	= 28	ADDL. STAGE WT. - LBS.	= 130
MAX. OPERATING - P.S.I.	= 400	DISCH. - IN.	= 8.10.12
STD. LATERAL - IN.	= 0.56	SUCTON - IN.	= 8
STD. SHAFT DIA. - IN.	= 1.938	BOWL CONN. FLANGED COLLET	
MAX. SHAFT DIA. - IN.	= —	ADD 1" PER ADDITIONAL STAGE	
MIN. SUBMERGENCE - IN.	= 24		



Curves reflect typical performance; refer to factory for certification.