


CURVE data**Verli-Line®**


No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-1
2	-1	IMP. - NI-RI	-1
3	0	BOWL - BRZ.	-2
5	1	BOWL - NI-R.	-2

18EHH**1770** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE ()
STAGE STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 45.0	IMPELLER WT. - LBS.	= 63
W/P PER IMPELLER LB.-FT ²	= 6.56	ONE STAGE WT. - LBS.	= 750
MAX. SPHERE SIZE	= -----	ADDL STAGE WT. - LBS.	= 325
MAX. NO. STD. STAGES	= 10	IMPELLER NUMBER	=
MAX. OPERATING - P.S.I.	= 500	DISCH. - IN.	= 14 CD
STD. LATERAL - IN.	= 560	SUCTION - IN.	= 12
STD. SHAFT DIA. - IN.	= 2-3/16	MAX. LATERAL IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. FLANGED - COLLET	=
MIN. SUBMERGENCE - IN.	= 30	ADD 14" PER ADDITIONAL STAGE.	=



Curves reflect typical performance. Refer to factory for confirmation.