


CURVE data**Verli-Line®**


No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-1
2	-1	IMP. - NI-RI	-1
3	0	BOWL - BRZ.	-2
5	1	BOWL - NI-R.	-2

18FXHHM**1770** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE ()
STAGE STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 53.7	IMPELLER WT. - LBS.	= 58
WHP PER IMPELLER LB.-FT. ²	= 6.36	ONE STAGE WT. - LBS.	= 975
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 375
MAX. NO. STD. STAGES	= 10	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 350	DISCH. - IN.	= 14 OD
STD. LATERAL - IN.	= 560	SUCTION - IN.	= 14 OD
STD. SHAFT DIA. - IN.	= 2-3/16	MAX LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. FLANGED COLLET	
MIN. SUBMERGENCE - IN.	= 32	ADD 14" PER ADDITIONAL STAGE	



Curves reflect typical performance, refer to factory for verification.