


CURVE data**Verli-Line®**

No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-1
2	-2	IMP. - NI-RI	-1
3	-1	BOWL - BRZ.	-3
4	0	BOWL - NI-R.	-3


6AWM**1750**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 4 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 4 STAGE EFFICIENCY CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE ()
STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 6.28	IMPELLER WT. - LBS.	= 2.3
W.P. PER IMPELLER LB.-FT.	= 0.03	ONE STAGE WT. - LBS.	= 60
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 16
MAX. NO. STD. STAGES	= 15	IMPELLER NUMBER	= -----
MAX. OPERATING - PSI	= 400	DISCH. - IN.	= 4
STD. LATERAL - IN.	= 0.25	SUCTION - IN.	= 4
STD. SHAFT DIA. - IN.	= 1.00	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. THREADED - COLLET	
MIN. SUBMERGENCE - IN.	= 18	ADD 5-1/4" PER ADDITIONAL STAGE.	



VL1750AWM1110