


CURVE data

Verli-Line®


No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-2	IMP. - C.I.	-2
2	-2	IMP. - NI-RI	-1
3	-1	BOWL - BRZ.	-1
4	0	BOWL - NI-R.	-1

6 BHLC**1750** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 4 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 4 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE ()
STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 3.88	IMPELLER WT. - LBS.	= 2.8
WR. PER IMPELLER LB. - FT.	= 0.03	ONE STAGE WT. - LBS.	= 100
MAX. SPHERE SIZE	= 0.281	ADDL. STAGE WT. - LBS.	= 25
MAX. NO. STD. STAGES	= 50	IMPELLER NUMBER	= 3RK13
MAX. OPERATING - P.S.I.	= 530	DISCH. - IN.	= 4
STD. LATERAL - IN.	= 0.50	SUCTION - IN.	= 4
STD. SHAFT DIA. - IN.	= 1.00	MAX. LATERAL - IN.	=
MAX. SHAFT DIA. - IN.	= 1.00	BOWL CONN. - THREADED - COLLET	=
MIN. SUBMERGENCE - IN.	= 10	ADD 4-1/4" PER ADDITIONAL STAGE.	=



Curves reflect typical performance, refer to factory for certification.