


CURVE data**Verli-Line®**


No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-4	IMP. - C.I.	-2
2	-3	IMP. - NI-RI	-1
3	-2	BOWL - BRZ	-1
4	-1	BOWL - NI-R	-1

6 GRMC**1750** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 4 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 4 STAGE EFFICIENCY CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE ()
STAGE STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 3.38	IMPELLER WT. - LBS.	= 2.9
WR. PER IMPELLER LB.-FT ²	= 0.03	ONE STAGE WT. - LBS.	= 100
MAX. SPHERE SIZE	= —	ADD'L STAGE WT. - LBS.	= 25
MAX. NO. STD. STAGES	= 50	IMPELLER NUMBER	= —
MAX. OPERATING - P.S.I.	= 530	DISCH. - IN.	= 4
STD. LATERAL - IN.	= 0.36	SUCTION - IN.	= 4
STD. SHAFT DIA. - IN.	= 1.00	MAX. LATERAL - IN.	= —
MAX. SHAFT DIA. - IN.	= —	BOWL CONN. THREADED - COLLET	= —
MIN. SUBMERGENCE - IN.	= 9	ADD 4-1/4" PER ADDITIONAL STAGE.	= —



Curves reflect typical performance; refer to factory for certification.