


Verli-Line®

No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-5	IMP. - C.I.	-1
2	-3	IMP. - NI-RI	-1
5	0	BOWL - BRZ.	0
10	1	BOWL - NI-R.	-2


8EDXL**3500**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 5 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 5 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

 ONE ()
 STAGE STAGES
PUMP PERFORMANCE

EYE AREA - SQ. IN.	= 7.0	IMPELLER WT. - LBS.	= 8
WP. PER IMPELLER LB.-FT. ²	= 140	ONE STAGE WT. - LBS.	= 100
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 40
MAX. NO. STD. STAGES	= 45	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 400	DISCH. - IN.	= 5
STD. LATERAL - IN.	= 375	SUCTION - IN.	= 5
STD. SHAFT DIA. - IN.	= 1-3/16	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= 13	ADD 5' PER ADDITIONAL STAGE	



Curves reflect typical performance. refer to factory for certification