


CURVE data**Verti-Line**


No. Stages	Eff. Change	MATERIAL	Eff. Change
1	0	IMP. - C.I.	-1.0
2	0		
3	-1.0		
4	N/A		

57BRH**440** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE ()
STAGE STAGES**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 571	IMPELLER WT. - LBS.	= 975
WPI PER IMPELLER LB. FT. ²	= 1580	ONE STAGE WT. - LBS.	= 8000
MAX. SPHERE SIZE	= 5.25 IN.	ADD'L STAGE WT. - LBS.	= 4500
MAX. NO. STD. STAGES	= 3	IMPELLER NUMBER	= T7AWA99
MAX. OPERATING - P.S.I.	= -----	DISCH. - IN.	= 36
STD. LATERAL - IN.	= .62	SUCTION - IN.	= -----
STD. SHAFT DIA. - IN.	= RTF	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL IMP. CONN. - -----	= -----
MIN. SUBMERGENCE - IN.	= 126	ADD 23-1/2" PER ADDITIONAL STAGE.	



Curves reflect typical performance. refer to factory for certification.