

CURVE data


Verti-Line®

No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-1.0	IMP. - C.I.	-1.0
2	NO CHG.		
3	NO CHG.		
4	NO CHG.		


28BROHC**705**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.



EYE AREA - SQ. IN.	= 197.2	IMPELLER WT. - LBS.	= 190
WR. PER IMPELLER LB.-FT.	= 107.31	ONE STAGE WT. - LBS.	= 2420
MAX. SPHERE SIZE	= 1.91	ADD'L. STAGE WT. - LBS.	= 1210
MAX. NO. STD. STAGES	= 8	IMPELLER NUMBER	= T5NA268
MAX. OPERATING - P.S.I.	=	DISCH. - IN.	= 24
STD. LATERAL - IN.	= 1.06	SUCTION - IN.	=
STD. SHAFT DIA. - IN.	= 4	MAX. LATERAL - IN.	=
MAX. SHAFT DIA. - IN.	=	BOWL / IMP. CONN. -	
MIN. SUBMERGENCE - IN.	= 46	ADD 24-1/2" PER ADDITIONAL STAGE.	



Curves reflect typical performance; refer to factory for certification.