

CURVE data

Verli-Line®

No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-1
2	-1	IMP. - NI-RI	-1
3	0	BOWL - BRZ.	-2
5	1	BOWL - NI-R.	-2

20 EHM


880

R.P.M.


SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE ()
STAGES

PUMP PERFORMANCE



EYE AREA - SQ. IN.	= 61.2	IMPELLER WT. - LBS.	= 89
WT. PER IMPELLER LB.-FT. ²	= 10.94	ONE STAGE WT. - LBS.	= 920
MAX. SPHERE SIZE	= -----	ADD'L STAGE WT. - LBS.	= 425
MAX. NO. STD. STAGES	= 7	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 200	DISCH. - IN.	= 16 O.D.
STD. LATERAL - IN.	= .560	SUCTION - IN.	= 14 O.D.
STD. SHAFT DIA. - IN.	= 2.7/16	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= 33	ADD 15" PER ADDITIONAL STAGE	



Curves reflect typical performance, refer to factory for certification.