


Verli-Line®

No. Stages	Eff. Change	MATERIAL	Eff. Change
1	-3	IMP. - C.I.	-1
2	-1	IMP. - NI-R	-1
3	0	BOWL - BRZ.	-2
5	1	BOWL - NI-R.	-2


24EHM**880**

R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 3 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 3 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.

ONE
STAGE**PUMP PERFORMANCE**

EYE AREA - SQ. IN.	= 60.6	IMPELLER WT. - LBS.	= 135
WR. PER IMPELLER LB.-FT. ²	= 26.2	ONE STAGE WT. - LBS.	= 1150
MAX. SPHERE SIZE	= -----	ADDL. STAGE WT. - LBS.	= 650
MAX. NO. STD. STAGES	= 9	IMPELLER NUMBER	= -----
MAX. OPERATING - P.S.I.	= 200	DISCH. - IN.	= 16 OD
STD. LATERAL - IN.	= .800	SUCTION - IN.	= 16 OD
STD. SHAFT DIA. - IN.	= 2-11/16	MAX. LATERAL - IN.	= -----
MAX. SHAFT DIA. - IN.	= -----	BOWL CONN. - FLANGED - COLLET	
MIN. SUBMERGENCE - IN.	= 38	ADD 18" PER ADDITIONAL STAGE.	



Curves reflect typical performance; refer to factory for certification.